






















<p>CANON NETWORK CAMERA VB-S905F</p>		<p>9901B001 Indoor compact fixed box network camera. Fixed 2.7mm wide angle lens (96.0° AOV 16:9), digital night mode. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE. (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>
<p>CANON NETWORK CAMERA VB-S900F</p>		<p>8821B001 Indoor compact fixed box network camera. Fixed 2.7mm wide angle lens (96.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>
<p>CANON NETWORK CAMERA VB-S805D</p>		<p>9900B001 Indoor compact fixed dome network camera. Fixed 2.7mm wide-angle lens (95° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>
<p>CANON NETWORK CAMERA VB-M741LE</p>		<p>0312C001 Outdoor fixed box network camera with IR LED illumination up to 30m. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Pigtail cable connection. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting.</p>




CANON NETWORK CAMERA VB-M740E		0313C001	<p>Outdoor fixed box network camera. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 6 in-built video intelligent analytic functions. IP66, NEMA250-rated and operating temperature in -10° C to +55° C (-14° F to +131° F). Powered by PoE (Power supply not included) and SD/SDHC/SDHX Card slot for Edge storage. Pigtail cable connection. Available in Titanium White.</p> <p>Includes wall/ceiling plate for easy surface mounting.</p>
CANON NETWORK CAMERA VB-M720F		9909B001	<p>Indoor fixed box network camera with remote zoom configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>
CANON NETWORK CAMERA VB-H730F		9905B001	<p>Indoor fixed box network camera with remote Zoom configuration. 2.4x optical zoom and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports, and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>
Fixed Dome			
CANON NETWORK CAMERA VB-S800D		8820B001	<p>Indoor compact fixed dome network camera. Fixed 2.7mm wide-angle lens (95.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>





<p>CANON NETWORK CAMERA VB-M641VE</p>		<p>0308C001</p>	<p>Outdoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250 and IK10-rated and operating temperature in -40° C to +55° C (-40° F to +131° F) with optional heater fitted. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Pigtail cable connection. Available in Titanium White.</p> <p>Includes wall/ceiling plate for easy surface mounting. Optional heater unit HU641-VB sold separately.</p>
<p>CANON NETWORK CAMERA VB-M641V</p>		<p>0309C001</p>	<p>Indoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 8 in-built video & audio intelligent analytic functions, and linked events. IK10-rated. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White.</p> <p>Includes wall/ceiling plate for easy surface mounting.</p>
<p>CANON NETWORK CAMERA VB-M640VE</p>		<p>0310C001</p>	<p>Outdoor vandal resistant fixed dome network camera with PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 6 in-built video intelligent analytic functions. IP66, NEMA250 and IK10-rated and operating temperature in -10° C to +55° C (-14° F to +131° F). Powered by PoE (Power supply not included) and micro SD/SDHC/SDHX Card slot for Edge storage. Pigtail cable connection. Available in Titanium White.</p> <p>Includes wall/ceiling plate for easy surface mounting.</p>




<p>CANON NETWORK CAMERA VB-M640V</p>		<p>0311C001</p>	<p>Indoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 6 in-built video intelligent analytic functions. IK10-rated. Powered by PoE (Power supply not included) and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Supplied with wall/ceiling mounting plate.</p>
<p>CANON NETWORK CAMERA VB-M620VE</p>		<p>9907B001</p>	<p>Outdoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. IP66 and IK10-rated and operating temperature in -30° C to +50° C (-22° F to + 122° F) with optional heater fitted. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver. Optional heater unit HU600-VB sold separately.</p>
<p>CANON NETWORK CAMERA VB-H651V</p>		<p>1385C001</p>	<p>Outdoor vandal resistant fixed dome network camera with IR LED illumination up to 20m, and NTSC video out for manual PT configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250 and IK10-rated and operating temperature in -40° C to +55° C (-40° F to +131° F) with optional heater fitted. Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting. Optional heater unit HU652-VB sold separately.</p>

CANON NETWORK CAMERA VB-H630VE		9903B001 Outdoor vandal resistant fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. IP66 and IK10-rated and operating temperature in -30 ^o C to +50 ^o C (-22 ^o F to +122 ^o F) with optional heater fitted. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver. Optional heater unit HU600-VB sold separately.
CANON NETWORK CAMERA VB-H630D		9904B001 Indoor fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.
CANON NETWORK CAMERA VB-M620D		9908B001 Indoor fixed dome network camera with remote PTRZ configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.
PTZ Dome		
CANON NETWORK CAMERA VB-S31D		8819B001 Indoor compact network camera with lite-PT operation. Fixed 2.7mm wide angle lens (95.0° AOV 16:9) and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.

<p>CANON NETWORK CAMERA VB-S30D</p>		<p>8818B001</p>	<p>Indoor compact network camera with lite-PTZ operation. 3.5x optical zoom, auto focus, and digital night mode. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>
<p>CANON NETWORK CAMERA VB-R13VE</p>		<p>1381C001</p>	<p>Outdoor vandal resistant PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. 12cm Pigtail cable connection. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.</p>
<p>CANON NETWORK CAMERA VB-R13</p>		<p>1383C001</p>	<p>Indoor PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions, and linked events. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes ceiling plate for easy surface mounting.</p>

<p>CANON NETWORK CAMERA VB-R12VE</p>		<p>1382C001 Outdoor vandal resistant PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, day/night switching and Enhanced Digital Zoom capabilities. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 7 in-built video intelligent analytic functions. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.</p>
<p>CANON NETWORK CAMERA VB-R11VE</p>		<p>0305C001 Outdoor vandal resistant network PTZ Dome camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 9 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. 12cm Pigtail cable connection. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.</p>
<p>CANON NETWORK CAMERA VB-R11</p>		<p>0306C001 Indoor PTZ Dome network camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 9 in-built video & audio intelligent analytic functions, and linked events. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes ceiling plate for easy surface mounting.</p>

<p>CANON NETWORK CAMERA VB-R10VE</p>		<p>0307C001 Outdoor vandal resistant network PTZ Dome camera with 360° endless rotation, auto-flip, and auto-tracking capabilities. 30x optical zoom, auto focus and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology. 7 in-built video intelligent analytic functions. IP66, NEMA250, IK10-rated and operating temperature in -50° C to +55° C (-58° F to +131° F). Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Requires WM10-VB Wall mount, CM10-VB Ceiling mount, or PA10-15-VB Pipe mount - sold separately.</p>
<p>CANON NETWORK CAMERA VB-M50B</p>		<p>1064C001 Indoor PTZ network camera with 348° rotation and large aperture lens ideal for low light applications. 5x optical zoom, auto focus, day/night switching and Clear IR Mode. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast, ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 9 in-built video & audio intelligent analytic functions and linked events. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Only available in Black.</p>
<p>CANON NETWORK CAMERA VB-M42B</p>		<p>9906B002 Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Black (B).</p>
<p>CANON NETWORK CAMERA VB-M42</p>		<p>9906B001 Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max 1.3MP 720p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>

<p>CANON NETWORK CAMERA VB-H652LVE</p>		<p>1061C001</p>	<p>Outdoor vandal resistant fixed dome network camera with IR LED illumination up to 20m, and NTSC video out for manual PT configuration. 2.4x optical zoom, day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. ADSR - Area-specific Data Size Reduction technology and Motion-Adaptive Noise Reduction. 8 in-built video & audio intelligent analytic functions, and linked events. IP66, NEMA250 and IK10-rated and operating temperature in -40° C to +55° C (-40° F to +131° F) with optional heater fitted. Powered by PoE+, PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and micro SD/SDHC/SDHX Card slot for Edge storage. Available in Titanium White. Includes wall/ceiling plate for easy surface mounting. Optional heater unit HU652-VB sold separately.</p>
<p>CANON NETWORK CAMERA VB-H43B</p>		<p>9902B002</p>	<p>Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Black (B).</p>
<p>CANON NETWORK CAMERA VB-H43</p>		<p>9902B001</p>	<p>Indoor PTZ network camera with 340° rotation. 20x optical zoom, auto focus, and day/night switching. Multiple H.264 and Motion JPEG streams; max Full HD 1080p resolution at 30fps. Smart Shade Control - dynamic contrast. 6 in-built video & audio intelligent analytic functions. Powered by PoE, 24V AC and 12V DC (Power supply not included). Two way audio, Input/Output ports and SD/SDHC/SDHX Card slot for Edge storage. Available in Silver.</p>