



MOBILE ENERGY BASED ON LPG / NATURAL GAS

## SUNFIRE-REMOTE 400

ENERGY FOR  
THE FUTURE

DISTRIBUTED & INTEGRATED  
IN NORTH AMERICA BY



WWW.ENSOLSYSTEMS.COM  
TOLL-FREE: 1-877-583-6765



INTEGRATED  
POWER  
SYSTEMS FOR  
YOUR  
OFF-GRID  
APPLICATIONS.  
CUSTOM  
ENGINEERED  
TO MEET YOUR  
NEEDS.



### PRODUCT

The Sunfire-Remote series includes power generators which are very efficient converters for LPG or natural gas in the range of 400 to 1,200 watt. These systems based on solid oxide fuel cells (SOFC) have an electrical efficiency of up to 35%, almost twice those of generators using petrol or diesel engines. Additionally, the systems do not emit any pollutants, just small amounts of carbon dioxide, and are very quiet while operating.

### APPLICATIONS

Continuous off-grid power supply in any stationary and mobile application:

- + Oil & Gas: monitoring and measuring systems
- + Telecommunication: radio transmitter
- + Security: emergency power systems, construction sites, wind turbines under construction

### REFERENCES

Deutsche Bahn AG

- + Reliable power for a level crossing signal system since November 2017 (> 14 months uninterrupted power supply)
- + 400 W SOFC system + PV

Mount Everest base camp

- + Supplying power to an infrared cabin of Physiotherm at a height of about 5,300 m
- + 800 W SOFC system + PV

### CORE ADVANTAGES

- + **Highest efficiency:** Up to 35%<sub>el</sub> leading to low fuel consumption and reduced logistics
- + **Reliability:** Suitable for harsh climatic conditions
- + **Long maintenance intervals:** Durable power supply for months
- + **Independent:** Off-grid power at any time and any weather conditions
- + **Environmental-compatible:** Low emissions, quiet operation without vibrations

MOBILE ENERGY BASED ON LPG / NATURAL GAS

## SUNFIRE-REMOTE 400 – TECHNICAL DATA



SUNFIRE-REMOTE 400	
Electrical power	350 W
Daily electrical capacity	8.4 kWh / day
Electrical power nominal	150 – 350 W
Rated voltage	24 V <sub>DC</sub>
Fuel	Propane / natural gas
Fuel consumption	part load 74 g / h (0.95 kW) – full load 101 g / h (1.3 kW)
Gas connection	8 mm
Pressure of gas connection	15 – 50 mbar
Weight	40 kg
Dimensions	550 × 480 × 400 mm
Ambient temperature for operation	-20 °C to +40 °C
Water / lubricant consumption	none
Noise emission	<50 db(A)
IP protection category	IP20
Communication	Ethernet TCP / IP
System scope	Sunfire SOFC core system, battery management, desulfurization cartridge, Exhaust tube 1 m
Essential accessories for operation	Battery VRLA 24 V, > 300 Ah

Sunfire Fuel Cells GmbH reserves the right to make changes at any time without notice, in materials, equipment, specifications and models shown in any document. Specifications are subject to technical changes. Images do not necessarily show the equipment that will be installed. All data are for reference only. Performance data are not to be used for guarantee purposes. Version 02/2020